



(metal mania™)

a collection of decorative accents

(metal mania™)



bronze

Chair Rail 1 7/8" x 13" - Link Liner 9/16" x 13"
Also shown Essentials Basic Black 12" x 24"

Go a little design crazy with Metal Mania, the latest Marazzi USA decorative metallic collection. Six distinctive designs and two burnished metal colors – Bronze and Pewter – are high impact additions to any wall. Used singly or in combination, these head-turning decos add the finishing touch to a room, expressing the individual personality of the owner or designer.



ULLP Bronze
Pencil Liner
5/8"x13"



ULLT Bronze
Wave Liner
3/4"x13"



ULLV Bronze
Link Liner
9/16"x13"



ULLR Bronze
Ridged Liner
9/16"x13"



ULLX Bronze
Dot Liner
1 7/8"x13"



ULLM Bronze
Chair Rail
1 7/8"x13"



ULLQ Pewter
Pencil Liner
5/8"x13"



ULLU Pewter
Wave Liner
3/4"x13"



ULLW Pewter
Link Liner
9/16"x13"



ULLS Pewter
Ridged Liner
9/16"x13"



ULLY Pewter
Dot Liner
1 7/8"x13"



ULLN Pewter
Chair Rail
1 7/8"x13"

technical

ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	2.0% to 5.0%	0.5% to 3.0%	C373
Frost Resistance	As Reported	Not Resistant	C1026
Scratch Resistance	MOHS 1-10	5	MOHS Scale
Abrasion Resistance	Class 0 - Class V	Class 0	C1027
DCOF-Dynamic Coefficient of Friction (Wet Areas Only)*	As Reported	N/A	DCOF AcuTest SM **
SCOF-Static Coefficient of Friction (Dry)	As Reported	N/A	C1028
SCOF-Static Coefficient of Friction (Wet)	As Reported	N/A	C1028
Chemical Resistance	Class A - Class E	Class B	C650
Stain Resistance	Class A - Class E	Class A	C1378

*Dynamic Coefficient of Friction (DCOF) - Water, oil, grease or other fluids create slippery conditions. When installing floors in areas with exposure to these conditions, a minimum D.C.O.F. value of 0.42 is required. Additionally, extra caution is required with regards to product selection and proper maintenance. Visit www.tcnatile.com for complete information regarding the DCOF Acutest test method and values.

**DCOF AcuTest is the industry designation for the test procedure contained in ANSI A137.1 Section 9.6, which has been extensively researched, allows for in-situ field measurements, and is in use at tile manufacturing facilities. It was so named to distinguish it from other DCOF measurements using different instruments and/or protocols.

APPLICATIONS

- All Metal Mania™ liners and chair rail are recommended for use in residential/ light commercial, interior wall applications.
- Metal Mania™ is not recommended for use on countertops.
- Metal Mania™ can be installed and used in wet areas such as backsplashes, bathroom walls and showers. This collection is not recommended for use in swimming pools.
- Metal Mania™ is not recommended in areas where temperatures rise above 242 °F.
- Metal Mania™ should be installed a minimum of 25" from direct flames.


CARE AND MAINTENANCE






- Clean regularly with clear water and/or neutral (soapless) cleaner, wipe dry with soft cloth.
- Do not use sandpaper, steel wool, scouring pads or any other abrasive materials.

INSTALLATION INSTRUCTIONS

- Install using a Polymer based adhesive (Liquid latex/polymer reinforced high quality Portland cement grout, water cleanable epoxy grout etc.).
- Follow adhesive manufacturer's instructions for preparation, application and clean up.
- It is recommended to cover the tiles upper surface with painters tape prior to grouting for easier clean up.
- Residue should be removed immediately after grouting.
- If tile requires cutting, apply protective varnish to the cut side. Wait 24 hours to allow curing prior to installing and grouting the application.

packaging

	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Chair Rail	1 7/8"x13"	10		11	Compatible
Pencil Liner	5/8"x13"	10		3	Compatible
Ridged Liner	9/16"x13"	10		2	Compatible
Wave Liner	3/4"x13"	10		3	Compatible
Link Liner	9/16"x13"	10		2	Compatible
Dot Liner	1 7/8"x13"	10		7	Compatible

-  Wall Tile
-  Decorative Tile
-  Trim Available
-  Very Uniform Appearance
-  Abrasion Resistance





American Marazzi Tile, Inc.
Headquarters & Manufacturing Plant

359 Clay Road East
Sunnyvale, Texas 75182

T 972.226.0110
F 972.226.5629
www.marazzitile.com
contact@marazzitile.com



Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.