

**MARAZZI**  USA

the fine art of porcelain stoneware

**(timeless collection)**

color body porcelain stoneware  
rectified |  printing technique

Made In The USA




Calacatta Pearl



Emperador Mocha



Mosaic Hexagon 1 3/4" x 1 1/2"



Mosaic Hexagon 1 3/4" x 1 1/2"



Mosaic Hexagon 1 3/4" x 1 1/2"



Catwalk Random Mosaic  
Walnut Wedge 12" x 12"



Catwalk Random Mosaic  
Pecan Pump 12" x 12"



Catwalk Random Mosaic  
Olive Oxfords 12" x 12"



## Decorative Options

### Romance Collection

Venetian Bronze Venetian Bronze Venetian Bronze  
Dot Insert Dot Insert Chair Rail  
2"x2" 1"x1" 1 1/2"x13"



Venetian Bronze  
Dot Listelli  
1"x13"



Venetian Bronze  
Pencil Liner  
1/2"x13"



Bronze  
Dot Insert  
2"x2"



Bronze  
Dot Insert  
1"x1"



Bronze  
Chair Rail  
1 1/2"x13"



Bronze  
Dot Listelli  
1"x13"



Bronze  
Pencil Liner  
1/2"x13"



Nickel  
Dot Insert  
2"x2"



Nickel  
Dot Insert  
1"x1"



Nickel  
Chair Rail  
1 1/2"x13"



Nickel  
Dot Listelli  
1"x13"



Nickel  
Pencil Liner  
1/2"x13"



Contributes to LEED Credits **made in the USA**

	MODULAR TILE					FLOOR TILE					DECOS™					TRIMS™		
Thickness	3 1/4" x 6 1/2" R Rectified (8.1 x 16.5 cm) 5/16" (8.5mm)	13" x 13" R Rectified (33.3 x 33.3 cm) 5/16" (8.5mm)	20" x 20" R Rectified (50.8 x 50.8 cm) 7/16" (11mm)	12" x 24" R Rectified (30.5 x 60.9 cm) 7/16" (11mm)	18" x 36" R Rectified (45.7 x 91.4 cm) 3/8" (9mm)	1" x 1" Dot Insert (2.5 x 2.5 cm)	2" x 2" Dot Insert (5 x 5 cm)	1" x 13" Dot Listelli (2.5 x 33.3 cm)	12" x 12" Mosaic - Hexagon (30 x 30 cm)	13" x 13" Mosaic - Hexagon (33.3 x 33.3 cm)	1/2" x 13" Pencil Liner (1.25 x 33.3 cm)	1 1/2" x 13" Chair Rail (1.57 x 33.3 cm)	3" x 13" Buttose					
Names (colors)	Calacatta Pearl (white)	UK2N	UK2A	UK2D	UK2K	ULCP				UK2V				UK2S				
Emperador Mocha (Brown)	UK2R	UK2C	UK2F	UK2M	ULCR				UK2X				UK2U					
Marfil Cream (beige)	UK2P	UK2B	UK2E	UK2L	ULCQ				UK2W			UK2T						
Bronze						UJ7B	UJ6T	UJ9E			UJ6R	UJ6P						
Nickel						UJ7A	UJ6S	UJ9D			UJ6Q	UJ6N						
Venetian Bronze						UJ7C	UJ68	U9F			UJ7U	UJ7S						
Walnut Wedge										UJ93								
Pecan Pump										UJ9W								
Olive Oxfords										UJ9V								

Notes: \* Mosaics are mounted to a mesh backing.  
\*\* Trim is available in all colors and made to complement Modular and Floor Tile.

## ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	7	MOHS Scale
Breaking Strength	≥ 250 lbf.	416	C648
Facial Dimension	-3.0% < Nominal ≤ 2.0%	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (squareness)	+/- 0.25% or +/- 0.8 mm**	Within Standard	C502
Warpage (flatness)	+/- 0.40% or +/- 1.3 mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
DCOF-Dynamic Coefficient of Friction (Wet Areas Only) <sup>†</sup>	As Reported	Minimum 0.42	DCOF AcuTest <sup>SM</sup>
SCOF-Static Coefficient of Friction (Dry)	As Reported	0.80 ≤ C.O.F. < 0.90	C1028
SCOF-Static Coefficient of Friction (Wet)	As Reported	0.60 ≤ C.O.F. < 0.70	C1028
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

<sup>†</sup>Dynamic Coefficient of Friction (DCOF) - Water, oil, grease or other fluids create slippery conditions. When installing floors in areas with exposure to these conditions, a minimum D.C.O.F. value of 0.42 is required. Additionally, extra caution is required with regards to product selection and proper maintenance. Visit [www.tcnatiles.com](http://www.tcnatiles.com) for complete information regarding the DCOF Acutest test method and values.

<sup>SM</sup>DCOF AcuTest is the industry designation for the test procedure contained in ANSI A137.1 Section 9.6, which has been extensively researched, allows for in-situ field measurements, and is in use at tile manufacturing facilities. It was so named to distinguish it from other DCOF measurements using different instruments and/or protocols.

\*\* Whichever is less

