

MARAZZI  USA

the fine art of porcelain stoneware



**(treverkchic)**

color body porcelain stoneware | rectified |  printing technique



**africa**

8"x48"

(treverkchic)



*The exemplary rendition of natural fine wood graining and contemporary colorations in Treverkchic by Marazzi USA elevates its standing in the wood-look porcelain hierarchy. Authentic visuals and textures translate the warmth of hand-crafted wood to easy-care porcelain.*



**italiano**

6"x48" - 8"x48"



**americano**

6"x48"



Luxe linears connote refined traditional woods that have been revitalized with energized shades to fit right in with current residential and hospitality trends for graceful geometries.

The natural warmth and tactile appeal of the noble walnuts and teaks that inspired the series are beautifully translated to rectified, easy-care, color-body porcelain that's très moderne, with très equaling "very."



**MH2S Africa**  
12"x48" Rectified



**MH2Y Africa**  
8"x48" Rectified



**MH34 Africa**  
6"x48" Rectified



**MH2N Francese**  
12"x48" Rectified



**MH2U Francese**  
8"x48" Rectified



**MH30 Francese**  
6"x48" Rectified

## technical

### ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 1005 lbf.	C648
Facial Dimension	-3.0% < Nominal ≤ 2.0%	Within Standard	C499
Thickness	≤ 0.04 in (1.02 mm max)	Within Standard	C499
Wedging (squareness)	+/- 0.25% or +/- 0.8 mm**	Within Standard	C502
Warpage (flatness)	+/- 0.40% or +/- 1.8 mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
DCOF-Dynamic Coefficient of Friction (Wet Areas Only) <sup>†</sup>	As Reported	Minimum 0.42	DCOF AcuTest <sup>SM</sup> **
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

<sup>†</sup>Dynamic Coefficient of Friction (DCOF) - Water, oil, grease or other fluids create slippery conditions. When installing floors in areas with exposure to these conditions, a minimum D.C.O.F. value of 0.42 is required. Additionally, extra caution is required with regards to product selection and proper maintenance. Visit [www.tcnatile.com](http://www.tcnatile.com) for complete information regarding the DCOF AcuTest test method and values.  
<sup>\*\*</sup>DCOF AcuTest is the industry designation for the test procedure contained in ANSI A137.1 Section 9.6, which has been extensively researched, allows for in-situ field measurements, and is in use at tile manufacturing facilities. It was so named to distinguish it from other DCOF measurements using different instruments and/or protocols.  
<sup>\*\*</sup> Whichever is less

Floor Tile

Wall Tile

3d Printing Technique

Rectified Tile

Suitable for Outdoors

Moderate Variation

Frost Resistant

Abrasion Resistance

D.C.O.F. (Wet Areas)  
(Minimum 0.42)

25% Minimum Pre-Consumer  
Recycled Content

No VOC



Contributes to  
LEED Credits



**MH2M** Italiano  
12"x48" Rectified



**MH2T** Italiano  
8"x48" Rectified



**MH2Z** Italiano  
6"x48" Rectified



**MH2P** Americano  
12"x48" Rectified





**MH2V** Americano  
8"x48" Rectified



**MH31** Americano  
6"x48" Rectified

packaging

	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Floor Tile	6"x48" R	6	11.63	58	0.394
Floor Tile	8"x48" R	3	7.75	40	0.394
Floor Tile	12"x48" R	3	11.60	60	0.394

	Sizes	Ctn	Sq. Ft.	Weight (lbs.)
Floor Tile	6"x48" R	24	279.12	1392
Floor Tile	8"x48" R	40	310.00	1600
Floor Tile	12"x48" R	20	232.60	1200



American Marazzi Tile, Inc.  
Headquarters & Manufacturing Plant

359 Clay Road East  
Sunnyvale, Texas 75182

T 972.226.0110  
F 972.226.5629  
[www.marazzitile.com](http://www.marazzitile.com)  
[contact@marazzitile.com](mailto:contact@marazzitile.com)



Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.