

Baby Beach




Blue Beach



Crane Beach



Eagle Beach



Grace Beach



Shoal Bay



DECOS®

12½"x13"

(32x33.3 cm)

1/8" (3 mm)

Thickness

Names (colors)

Baby Beach (olive)

ULMV

Blue Beach (teal)

ULMW

Crane Beach (blue/brown)

ULMX

Eagle Beach (tigers eye)

ULMY

Grace Beach (grey blue)

ULMZ

Shoal Bay (beige/taupe)

ULN2



Wall  
Tile



Decorative  
Tile



Suitable for  
Outdoors



Slight  
Variation



Frost  
Resistant



Abrasion  
Resistance



ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	≤ 0.50%	≤ 0.50%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	5.5	MOHS Scale
Abrasion Resistance	Class 0 - Class V	Class 0	C1027
DCOF-Dynamic Coefficient of Friction (Wet Areas Only)*	As Reported	N/A	DCOF AcuTest <sup>SM</sup> **
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

\*Dynamic Coefficient of Friction (DCOF) - Water, oil, grease or other fluids create slippery conditions. When installing floors in areas with exposure to these conditions, a minimum D.C.O.F. value of 0.42 is required. Additionally, extra caution is required with regards to product selection and proper maintenance. Visit [www.tcnatile.com](http://www.tcnatile.com) for complete information regarding the DCOF AcuTest test method and values.

\*\*DCOF AcuTest is the industry designation for the test procedure contained in ANSI A137.1 Section 9.6, which has been extensively researched, allows for in-situ field measurements, and is in use at tile manufacturing facilities. It was so named to distinguish it from other DCOF measurements using different instruments and/or protocols.

\*\* Whichever is less