



(livigno™)

glazed ceramic tile



grigio

18"x18" - 3"x12" Bullnose



oro

12"x12" - 3"x12" Bullnose

In the natural world, erosion by environmental elements smooths the surface of rock until it's satiny and reveals intriguing shades and textures beneath. Livigno™ by Marazzi USA captures that ever-changing look of primal weathered stone in modern, easy-to-install, easy-to-clean ceramic tile engineered for interior residential installations.



noce

18"x18" - 12"x12" Mosaic Square 2"x2" - 3"x12" Bullnose



Visual variety within an array of earthen colors holds the promise of an affordable format with designer possibilities. Widely-ranged tones of golden brown, grey and walnut evoke the true shadings and variations found within the earth's strata. Livigno depicts these natural fractures and fissures with amazing accuracy; fine lines dissect the tile's surface while evidence of stone residues appears randomly dispersed. Clean, straight edges keep this stone look relevant for modern lifestyles.

Warm, earthy colors comprise the series, making it a perfect foil for more adventurous, more colorful home furnishings and accent pieces that express individuality and design flair. Two generous sizes 12"x12" and 18"x18" with accompanying 2"x2" mesh-mounted mosaic sheets and 3"x12" bullnose trim take the floor – and walls and counter tops and baths and . . . wherever the imagination soars.



Grigio



Noce



ULDE Grigio
18"x18"



ULDB Grigio
12"x12"




ULDF Noce
18"x18"



ULDC Noce
12"x12"



ULDH Grigio
Mosaic - Square 2"x2"
12"x12"



ULDJ Noce
Mosaic - Square 2"x2"
12"x12"

Trims



ULDL Grigio
Bullnose
3"x12"



ULDM Noce
Bullnose
3"x12"

technical

ASTM Test Results

Technical Characteristics	ASTM Standards	ASTM Test Results	ASTM Test Methods
Water Absorption	3.0% - 7.0%	2.0% - 5.0%	C373
Frost Resistance	As Reported	Resistant	C1026
Scratch Resistance	MOHS 1-10	6.5	MOHS Scale
Breaking Strength	≥ 250 lbf.	≥ 385 lbf.	C648
Facial Dimension	+/- 3.0% From Nominal	Within Standard	C499
Thickness	≤ 0.40 in (1.02 mm max)	Within Standard	C499
Wedging (squareness)	+/- 0.50% or +/- 2.0 mm**	Within Standard	C502
Warpage (flatness)	+/- 0.75% or +/- 2.0 mm**	Within Standard	C485
Abrasion Resistance	Class 0 - Class V	Class IV	C1027
DCOF-Dynamic Coefficient of Friction (Wet Areas Only) [†]	As Reported	Less Than 0.42	DCOF AcuTest SM
Chemical Resistance	Class A - Class E	Class A	C650
Stain Resistance	Class A - Class E	Class A	C1378

[†]Dynamic Coefficient of Friction (DCOF) - Water, oil, grease or other fluids create slippery conditions. When installing floors in areas with exposure to these conditions, a minimum D.C.O.F. value of 0.42 is required. Additionally, extra caution is required with regards to product selection and proper maintenance. Visit www.tcnatile.com for complete information regarding the DCOF AcuTest test method and values.

^{**}DCOF AcuTest is the industry designation for the test procedure contained in ANSI A137.1 Section 9.6, which has been extensively researched, allows for in-situ field measurements, and is in use at tile manufacturing facilities. It was so named to distinguish it from other DCOF measurements using different instruments and/or protocols.

** Whichever is less

- Floor Tile
- Wall Tile
- Decorative Tile
- Trim Available
- Substantial Variation
- Frost Resistant
- Abrasion Resistance
- 7% Minimum Pre-Consumer Recycled Content
- No VOC



Contributes to
LEED Credits
made in the
USA



Oro



ULDD Oro
18"x18"



ULDA Oro
12"x12"



ULDG Oro
Mosaic - Square 2"x2"
12"x12"



ULDK Oro
Bullnose
3"x12"

Decorative Options



UJ6U Nickel
Floral Insert
4"x4"



UJ62 Nickel
Diamond Insert
4"x4"



UJ6V Bronze
Floral Insert
4"x4"



UJ63 Bronze
Diamond Insert
4"x4"



UJ6W Nickel
Floral Insert
2"x2"



UJ64 Nickel
Diamond Insert
2"x2"



UJ6X Bronze
Floral Insert
2"x2"



UJ65 Bronze
Diamond Insert
2"x2"



UJ7E Nickel
Fleur de Lis Insert
2"x2"



UJ6S Nickel
Dot Insert
2"x2"



UJ7F Bronze
Fleur de Lis Insert
2"x2"



UJ6T Bronze
Dot Insert
2"x2"



UJ6Y Nickel
Floral Insert
1"x1"



UJ66 Nickel
Diamond Insert
1"x1"



UJ6Z Bronze
Floral Insert
1"x1"



UJ67 Bronze
Diamond Insert
1"x1"



UJ89 Nickel
Fleur de Lis Insert
1"x1"



UJ7A Nickel
Dot Insert
1"x1"





UJ9A Bronze
Fleur de Lis Insert
1"x1"



UJ7B Bronze
Dot Insert
1"x1"

packaging

	Sizes	Pcs	Sq. Ft.	Weight (lbs.)	Thickness
Floor Tile	12"x12"	15	14.53	50	0.315
Floor Tile	18"x18"	8	17.44	66	0.354
Mosaic - Square 2"x2"	12"x12"	10	9.69	39	Compatible
Insert	1"x1"	10		1	Compatible
Insert	2"x2"	8		1	Compatible
Insert (Floral)	4"x4"	8		7	Compatible
Insert (Diamond)	4"x4"	8		2	Compatible
Bullnose	3"x12"	20		21	Compatible

	Sizes	Ctn	Sq. Ft.	Weight (lbs.)
Floor Tile	12"x12"	48	697.44	2400
Floor Tile	18"x18"	32	558.08	2156



American Marazzi Tile, Inc.
Headquarters & Manufacturing Plant

359 Clay Road East
Sunnyvale, Texas 75182

T 972.226.0110
F 972.226.5629
www.marazzitile.com
contact@marazzitile.com



Color and other aesthetic features shown are as close as the limitation of the printing process will allow. We have tried to make this brochure as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in colors, materials, packaging, specifications and availability. Since some information may have been updated since time of printing, please check with American Marazzi Tile Customer Service for details.